

Chapter 6 Specifications

DC Characteristics

Accuracy Specifications: \pm (% of reading + % of range) ^[1]						
Function	Range ^[2]	Test Current or Load Voltage	24 Hour ^[3] $T_{CAL}^{\circ}\text{C} \pm 1^{\circ}\text{C}$	90 Day $T_{CAL}^{\circ}\text{C} \pm 5^{\circ}\text{C}$	1 Year $T_{CAL}^{\circ}\text{C} \pm 5^{\circ}\text{C}$	Temperature Coefficient 0°C to $(T_{CAL}^{\circ}\text{C}-5^{\circ}\text{C})$ $(T_{CAL}^{\circ}\text{C}+5^{\circ}\text{C})$ to 50°C
DC Voltage	200.0000mV	-	0.0020 + 0.0020	0.0030 + 0.0025	0.0040 + 0.0025	0.0005 + 0.0005
	2.000000V	-	0.0015 + 0.0005	0.0020 + 0.0006	0.0035 + 0.0006	0.0005 + 0.0001
	20.00000V	-	0.0020 + 0.0004	0.0030 + 0.0005	0.0040 + 0.0005	0.0005 + 0.0001
	200.0000V	-	0.0020 + 0.0006	0.0040 + 0.0006	0.0050 + 0.0006	0.0005 + 0.0001
	300.000V	-	0.0020 + 0.0006	0.0040 + 0.0010	0.0055 + 0.0010	0.0005 + 0.0001
DC Current	200.0000 μA	<0.03V	0.010 + 0.012	0.040 + 0.015	0.050 + 0.015	0.0020 + 0.0030
	2.000000mA	<0.25V	0.007 + 0.003	0.030 + 0.003	0.050 + 0.003	0.0020 + 0.0005
	20.00000mA	<0.07V	0.007 + 0.012	0.030 + 0.015	0.050 + 0.015	0.0020 + 0.0020
	200.0000mA	<0.7V	0.010 + 0.002	0.030 + 0.003	0.050 + 0.003	0.0020 + 0.0005
	1.000000A	<0.12V	0.050 + 0.020	0.080 + 0.020	0.100 + 0.020	0.0050 + 0.0010
	2.000000k Ω	1mA	0.0020 + 0.0005	0.008 + 0.001	0.010 + 0.001	0.0006 + 0.0001
	20.00000k Ω	100 μA	0.0020 + 0.0005	0.008 + 0.001	0.010 + 0.001	0.0006 + 0.0001
	200.0000k Ω	10 μA	0.0020 + 0.0005	0.008 + 0.001	0.010 + 0.001	0.0006 + 0.0001
	1.000000M Ω	2 μA	0.002 + 0.001	0.010 + 0.001	0.012 + 0.001	0.0010 + 0.0002
	10.00000M Ω	200nA	0.015 + 0.001	0.030 + 0.001	0.040 + 0.001	0.0030 + 0.0004
	100.0000M Ω	200nA 10M Ω	0.300 + 0.010	0.800 + 0.010	0.800 + 0.010	0.1500 + 0.0002

[1] Specifications are for 90-minute warm-up and 100 PLC integration time.

[2] 10% overrange on all ranges.

[3] Relative to calibration standards.

Measuring Characteristics**DC Voltage**

Input Impedance	200mV, 2V, 20V ranges: $10M\Omega$ or $>10G\Omega$ (For these ranges, input beyond ± 26 V are clamped through $106\text{ k}\Omega$) 200V and 300V ranges: $10M\Omega \pm 1\%$
Input Protection	300V
Input Offset Current	50pA, at 25°C , typical
CMRR (common mode rejection ratio)	140 dB for 1 $k\Omega$ unbalanced resistance in LO lead, ± 300 VDC peak maximum.
DC Current	
Shunt Resistor	100 Ω for 200 μA , 2 mA 1 Ω for 20 mA, 200 mA 0.1 Ω for 2 A

Auto Zero OFF Operation (typical value)

Following instrument warm-up at the environment temperature $\pm 1^\circ\text{C}$ and <5 minutes, add 0.0001 % range + 2 uV error for DCV and 2 m Ω error for resistance.

Settling Considerations

Reading settling times are affected by source impedance, cable dielectric characteristics and input signal changes. The default measurement delay can ensure the correctness of the first reading for most measurements.

Measurement Considerations

Teflon or other high-impedance, low-dielectric absorption wire insulation is recommended for these measurements.

AC Characteristics

Accuracy Specifications: \pm (% of reading + % of range) [1]

Function	Range ^[2]	Frequency Range	24 Hour ^[3] $T_{CAL}^{\circ}\text{C} \pm 1^{\circ}\text{C}$	90 Day $T_{CAL}^{\circ}\text{C} \pm 5^{\circ}\text{C}$	1 Year $T_{CAL}^{\circ}\text{C} \pm 5^{\circ}\text{C}$	Temperature Coefficient 0°C to $(T_{CAL}^{\circ}\text{C}-5^{\circ}\text{C})$ $(T_{CAL}^{\circ}\text{C}+5^{\circ}\text{C})$ to 50°C
True RMS AC Voltage^[4]	200.0000mV	3Hz- 5Hz	1.00 + 0.03	1.00 + 0.04	1.00 + 0.04	0.100 + 0.004
		5Hz-10Hz	0.35 + 0.03	0.35 + 0.04	0.35 + 0.04	0.035 + 0.004
		10Hz-20kHz	0.04 + 0.03	0.05 + 0.04	0.06 + 0.04	0.005 + 0.004
		20kHz-50kHz	0.10 + 0.05	0.11 + 0.05	0.12 + 0.05	0.011 + 0.005
		50kHz-100kHz	0.55 + 0.08	0.60 + 0.08	0.60 + 0.08	0.060 + 0.008
		100kHz- 300kHz	4.00 + 0.50	4.00 + 0.50	4.00 + 0.50	0.20 + 0.02
	2.000000V	3Hz-5Hz	1.00 + 0.02	1.00 + 0.03	1.00 + 0.03	0.100 + 0.003
		5Hz-10Hz	0.35 + 0.02	0.35 + 0.03	0.35 + 0.03	0.035 + 0.003
		10Hz-20kHz	0.04 + 0.02	0.05 + 0.03	0.06 + 0.03	0.005 + 0.003
		20kHz-50kHz	0.10 + 0.04	0.11 + 0.05	0.12 + 0.05	0.011 + 0.005
		50kHz-100kHz	0.55 + 0.08	0.60 + 0.08	0.60 + 0.08	0.060 + 0.008
		100kHz-300kHz	4.00 + 0.50	4.00 + 0.50	4.00 + 0.50	0.20 + 0.02
	20.00000V	3Hz-5Hz	1.00 + 0.03	1.00 + 0.04	1.00 + 0.04	0.100 + 0.004
		5Hz-10Hz	0.35 + 0.03	0.35 + 0.04	0.35 + 0.04	0.035 + 0.004
		10Hz-20kHz	0.04 + 0.04	0.07 + 0.04	0.08 + 0.04	0.008 + 0.004
		20kHz-50kHz	0.10 + 0.05	0.12 + 0.05	0.15 + 0.05	0.012 + 0.005
		50kHz-100kHz	0.55 + 0.08	0.60 + 0.08	0.60 + 0.08	0.060 + 0.008
		100kHz-300kHz	4.00 + 0.50	4.00 + 0.50	4.00 + 0.50	0.20 + 0.02
	200.0000V	3Hz-5Hz	1.00 + 0.02	1.00 + 0.03	1.00 + 0.03	0.100 + 0.003
		5Hz-10Hz	0.35 + 0.02	0.35 + 0.03	0.35 + 0.03	0.035 + 0.003
		10Hz-20kHz	0.04 + 0.02	0.07 + 0.03	0.08 + 0.03	0.008 + 0.003
		20kHz-50kHz	0.10 + 0.04	0.12 + 0.05	0.15 + 0.05	0.012 + 0.005
		50kHz-100kHz	0.55 + 0.08	0.60 + 0.08	0.60 + 0.08	0.060 + 0.008
		100kHz-300kHz	4.00 + 0.50	4.00 + 0.50	4.00 + 0.50	0.20 + 0.02
	300.000V	3Hz-5Hz	1.00 + 0.02	1.00 + 0.03	1.00 + 0.03	0.100 + 0.003
		5Hz-10Hz	0.35 + 0.02	0.35 + 0.03	0.35 + 0.03	0.035 + 0.003
		10Hz-20kHz	0.04 + 0.02	0.07 + 0.03	0.08 + 0.03	0.008 + 0.003

		20kHz-50kHz	0.10 + 0.04	0.12 + 0.05	0.15 + 0.05	0.012 + 0.005
		50kHz-100kHz	0.55 + 0.08	0.60 + 0.08	0.60 + 0.08	0.060 + 0.008
		100kHz-300kHz	4.0 + 0.50	4.0 + 0.50	4.0 + 0.50	0.20 + 0.02
True RMS AC Current [5]	200.0000 μ A	3Hz-5Hz	1.10 + 0.06	1.10 + 0.06	1.10 + 0.06	0.200 + 0.006
		5Hz-10Hz	0.35 + 0.06	0.35 + 0.06	0.35 + 0.06	0.100 + 0.006
		10Hz-5kHz	0.15 + 0.06	0.15 + 0.06	0.15 + 0.06	0.015 + 0.006
		5kHz-10kHz	0.35 + 0.70	0.35 + 0.70	0.35 + 0.70	0.030 + 0.006
	2.000000mA	3Hz-5Hz	1.00 + 0.04	1.00 + 0.04	1.00 + 0.04	0.100 + 0.006
		5Hz-10Hz	0.30 + 0.04	0.30 + 0.04	0.30 + 0.04	0.035 + 0.006
		10Hz-5kHz	0.12 + 0.04	0.12 + 0.04	0.12 + 0.04	0.015 + 0.006
		5kHz-10kHz	0.20 + 0.25	0.20 + 0.25	0.20 + 0.25	0.030 + 0.006
	20.00000mA	3Hz-5Hz	1.10 + 0.06	1.10 + 0.06	1.10 + 0.06	0.200 + 0.006
		5Hz-10Hz	0.35 + 0.06	0.35 + 0.06	0.35 + 0.06	0.100 + 0.006
		10Hz-5kHz	0.15 + 0.06	0.15 + 0.06	0.15 + 0.06	0.015 + 0.006
		5kHz-10kHz	0.35 + 0.70	0.35 + 0.70	0.35 + 0.70	0.030 + 0.006
	200.0000mA	3Hz-5Hz	1.00 + 0.04	1.00 + 0.04	1.00 + 0.04	0.100 + 0.006
		5Hz-10Hz	0.30 + 0.04	0.30 + 0.04	0.30 + 0.04	0.035 + 0.006
		10Hz-5kHz	0.10 + 0.04	0.10 + 0.04	0.10 + 0.04	0.015 + 0.006
		5kHz-10kHz	0.20 + 0.25	0.20 + 0.25	0.20 + 0.25	0.030 + 0.006
	1.000000A	3Hz-5Hz	1.10 + 0.06	1.10 + 0.06	1.10 + 0.06	0.100 + 0.006
		5Hz-10Hz	0.35 + 0.06	0.35 + 0.06	0.35 + 0.06	0.035 + 0.006
		10Hz-5kHz	0.15 + 0.06	0.15 + 0.06	0.15 + 0.06	0.015 + 0.006
		5kHz-10kHz	0.35 + 0.70	0.35 + 0.70	0.35 + 0.70	0.030 + 0.006
		5Hz-10Hz	0.35 + 0.08	0.35 + 0.10	0.35 + 0.10	0.035 + 0.008
		10Hz-5kHz	0.15 + 0.08	0.15 + 0.10	0.15 + 0.10	0.015 + 0.008

- [1] Specifications are for 90-minute warm-up, slow ac filter and sine wave input.
- [2] 10% overrange on all ranges.
- [3] Relative to calibration standards.
- [4] Specifications are for sine wave input >5% of range. For inputs from 1% to 5% of range and <50 kHz, add 0.1% of range additional error. For 50 kHz to 100 kHz, add 0.13% of range.
- [5] Specifications are for sine wave input >5% of range. For inputs from 1% to 5% of range, add 0.1% of range additional error. Specifications are typical values for 200 uA, 2 mA, 2 A and 10 A ranges when frequency is >1 kHz.

Measuring Characteristics**True RMS AC Voltage**

Measurement Method	AC-coupled True-RMS -- measure the ac component of input with up to 300 V DC bias on any range.
Crest Factor	≤ 5 at full range
Input Impedance	$1 \text{ M}\Omega \pm 2\%$, in parallel with $<150 \text{ pF}$ capacitance on any range
Input Protection	300 Vrms on all ranges
AC Filter Bandwidth	Slow: 3 Hz – 300 kHz Medium: 20 Hz – 300 kHz Fast: 200 Hz – 300 kHz
CMRR (common mode rejection ratio)	70 dB, for the $1 \text{ k}\Omega$ unbalance in LO lead, $<60 \text{ Hz}$ common mode signal frequency, $\pm 300 \text{ V}_{\text{peak}}$ maximum.

True RMS AC Current

Measurement Method	Direct coupled to the fuse and shunt; AC-coupled True RMS measurement (measure the AC component).
Crest Factor	≤ 3 at full range
Max. Input	DC + AC current peak value $<300\%$ of range. Current with DC current component $<1 \text{ Arms}$.
Shunt Resistor	$100 \text{ }\Omega$ for 200 uA, 2 mA $1 \text{ }\Omega$ for 20 mA , 200 mA $0.1 \text{ }\Omega$ for 1 A

Settling Time Considerations

The default measurement delay of the multimeter can ensure the correctness of the first readings of most of the measurements. Make sure the RC circuit of input terminal has been fully settled (about 1 s) before accurate measurement.

Frequency and Period Characteristics

Accuracy Specifications: \pm (% of reading) [1][2]						
Function	Range	Frequency Range	24 Hour ^[3] $T_{CAL}^{\circ}\text{C} \pm 1^{\circ}\text{C}$	90 Day $T_{CAL}^{\circ}\text{C} \pm 5^{\circ}\text{C}$	1 Year $T_{CAL}^{\circ}\text{C} \pm 5^{\circ}\text{C}$	Temperature Coefficient 0°C to $(T_{CAL}^{\circ}\text{C}-5^{\circ}\text{C})$ $(T_{CAL}^{\circ}\text{C}+5^{\circ}\text{C})$ to 50°C
Frequency, Period	200mV to 300V	3 Hz-5 Hz	0.07	0.07	0.07	0.005
		5 Hz-10 Hz	0.04	0.04	0.04	0.005
		10 Hz-40 Hz	0.02	0.02	0.02	0.001
		40 Hz-300 kHz	0.005	0.006	0.007	0.001
		300 kHz-1 MHz	0.005	0.006	0.007	0.001

Additional Low Frequency Errors: (% of reading)

Frequency	Gate Time (Resolution)			
	1 s (0.1 ppm)	0.1 s (1 ppm)	0.01 s (10 ppm)	0.001 s (100 ppm)
3 Hz-5Hz	0	0.12	0.12	0.12
5 Hz-10Hz	0	0.17	0.17	0.17
10 Hz-40Hz	0	0.20	0.20	0.20
40 Hz-100Hz	0	0.06	0.21	0.21
100 Hz-300Hz	0	0.03	0.21	0.21
300 Hz-1 kHz	0	0.01	0.07	0.07
>1kHz	0	0	0.02	0.02

[1] Specifications are for 90 minutes warm-up and 1 s gate time.

[2] For frequency \leq 300 kHz, the specification is for AC input voltage of 10% to 110% of range. For frequency $>$ 300 kHz, the specification is for AC input voltage of 20% to 110% of range. The maximum input is limited to 750 Vrms or 8×10^7 Volts-Hz (whichever is less). 200 mV range is full range input or input that is larger than the full range. For 20 mV to 200 mV inputs, multiply % of reading error by 10.

[3] Relative to calibration standards.

Measuring Characteristics**Frequency and Period**

Measurement Method	Reciprocal-counting technique, AC-coupled input using the AC voltage function.
Input Impedance	$1 \text{ M}\Omega \pm 2\%$, in parallel with $<150 \text{ pF}$ capacitance on any range
Input Protection	300 Vrms on all ranges

Measurement Considerations

All frequency counters are susceptible to error when measuring low-voltage, low-frequency signals. Shielding inputs from external noise pickup is critical for minimizing measurement errors.

Settling Considerations

Errors will occur when attempting to measure the frequency or period of an input following a dc offset voltage change. The input blocking RC time constant must be allowed to fully settle (about 1 s) before the most accurate measurements are possible.

Temperature Characteristics

Function	Probe Type	Type	Optimum Range	Accuracy Specifications ^[1]	
				1 Year $T_{CAL}^{\circ}\text{C} \pm 5^{\circ}\text{C}$	Temperature Coefficient 0°C to $(T_{CAL}^{\circ}\text{C}-5^{\circ}\text{C})$ $(T_{CAL}^{\circ}\text{C}+5^{\circ}\text{C})$ to 50°C
Temperature	RTD ^[2] (R_0 is within 49 Ω and 2.1 k Ω)	$a=0.00385$	-200 $^{\circ}\text{C}$ to 660 $^{\circ}\text{C}$	0.16 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$
		$a=0.00389$	-200 $^{\circ}\text{C}$ to 660 $^{\circ}\text{C}$	0.17 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$
		$a=0.00391$	-200 $^{\circ}\text{C}$ to 660 $^{\circ}\text{C}$	0.14 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$
		$a=0.00392$	-200 $^{\circ}\text{C}$ to 60 $^{\circ}\text{C}$	0.15 $^{\circ}\text{C}$	0.01 $^{\circ}\text{C}$
	Thermal Resistance	2.2 k Ω	-40 $^{\circ}\text{C}$ to 150 $^{\circ}\text{C}$	0.08 $^{\circ}\text{C}$	0.002 $^{\circ}\text{C}$
		3 k Ω	-40 $^{\circ}\text{C}$ to 150 $^{\circ}\text{C}$	0.08 $^{\circ}\text{C}$	0.002 $^{\circ}\text{C}$
		5 k Ω	-40 $^{\circ}\text{C}$ to 150 $^{\circ}\text{C}$	0.08 $^{\circ}\text{C}$	0.002 $^{\circ}\text{C}$
		10 k Ω	-40 $^{\circ}\text{C}$ to 150 $^{\circ}\text{C}$	0.08 $^{\circ}\text{C}$	0.002 $^{\circ}\text{C}$
	Thermocouple ^[3]	B	0 $^{\circ}\text{C}$ to 1820 $^{\circ}\text{C}$	0.76 $^{\circ}\text{C}$	0.14 $^{\circ}\text{C}$
		E	-270 $^{\circ}\text{C}$ to 1000 $^{\circ}\text{C}$	0.5 $^{\circ}\text{C}$	0.02 $^{\circ}\text{C}$
		J	-210 $^{\circ}\text{C}$ to 1200 $^{\circ}\text{C}$	0.5 $^{\circ}\text{C}$	0.02 $^{\circ}\text{C}$
		K	-270 $^{\circ}\text{C}$ to 1372 $^{\circ}\text{C}$	0.5 $^{\circ}\text{C}$	0.03 $^{\circ}\text{C}$
		N	-270 $^{\circ}\text{C}$ to 1300 $^{\circ}\text{C}$	0.5 $^{\circ}\text{C}$	0.04 $^{\circ}\text{C}$
		R	-50 $^{\circ}\text{C}$ to 1768.1 $^{\circ}\text{C}$	0.5 $^{\circ}\text{C}$	0.09 $^{\circ}\text{C}$
		S	-50 $^{\circ}\text{C}$ to 1768.1 $^{\circ}\text{C}$	0.6 $^{\circ}\text{C}$	0.11 $^{\circ}\text{C}$
		T	-270 $^{\circ}\text{C}$ to 400 $^{\circ}\text{C}$	0.5 $^{\circ}\text{C}$	0.03 $^{\circ}\text{C}$

[1] Specifications are for 90 minutes warm-up. Probe error excluded.

[2] Specification is for 4WR resistance measurement.

[3] Relative to cold junction temperature, accuracy is based on ITS-90. Built-in cold junction temperature refers to the temperature inside the banana jack and its accuracy is $\pm 2.5^{\circ}\text{C}$.

Measuring Characteristics

Thermocouple	
Conversion	ITS-90 software compensation
Reference Junction Type	Internal, Fixed, or External
T/C Check	Selectable per channel. When the channel resistance is $>5\text{k}\Omega$, it is considered as Open.
RTD	
Alpha	= 0.00385 (DIN/IEC 751): using ITS-90 software compensation; = 0.00389, 0.00391 or 0.00392: using IPTS-68 software□ compensation
Thermistor	44004, 44007, 44006 series
Measurement Considerations	
The built-in cold junction temperature tracks the temperature inside the terminal block. The change of temperature in the terminal block might cause additional error. When using the built-in cold junction compensation, connect the sensor terminal of the thermocouple to the terminal block and warm it up for more than 3 minutes to minimize the error.	

Module Specifications

MC3120/MC3132/MC3164/MC3324/MC3416/MC3648

	Multiplexer				Actuator	Matrix
General	MC3120	MC3132	MC3164	MC3324	MC3416	MC3648
Number of Channels	20	32	64	20 Voltage+4 Current	16	4×8
	2-wire	2/4 wire	1-wire	2-wire ^[3]	SPDT	2-wire
Connect to DMM Module?	Yes	Yes	Yes	Yes	No	No
Scanning Speed ^[1]	60Ch/s	60Ch/s	60Ch/s	60Ch/s	--	--
Open/Close Speed	200Ch/s	200Ch/s	200Ch/s	200Ch/s	200Ch/s	200Ch/s
Maximum Input						
Voltage (DC, AC rms)	300Vrms	300Vrms	300Vrms	300Vrms	300Vrms	300Vrms
Current (DC, AC rms)	1Arms	1Arms	1Arms	1Arms	2Arms	1Arms
Power (W, VA)	50VA	50VA	50VA	50VA	60VA	50VA
Isolation (ch-ch, ch-earth) (DC, AC rms)	300Vrms	300Vrms	300Vrms	300Vrms	300Vrms	300Vrms
DC Characteristics						
Offset Voltage	5uV	5uV	5uV	5uV	<3uV	5uV
Initial Closed Channel Resistance	<1Ω	<1Ω	<1Ω	<1Ω	<0.1Ω	<1Ω
Isolation (ch-ch, ch-earth)	>10GΩ	>10GΩ	>10GΩ	>10GΩ	>10GΩ	>10GΩ
AC Characteristics						
Bandwidth	1MHz	1MHz	1MHz	1MHz	1MHz	1MHz
Ch-Ch Cross Talk (dB) ^[2] 1MHz	-45	-45	-18 ^[3]	-45	-15	-18
Capacitance HI-LO	100pF	100pF	100pF	100pF	<500pF	100pF
Capacitance LO-Earth	200pF	200pF	200pF	200pF	<200pF	200pF

Volt-Hertz Limit	10^8	10^8	10^8	10^8	10^8	10^8
Other						
T/C Cold Junction Accuracy (Typical)	0.8°C	0.8°C	0.8°C ^[4]	0.8°C	--	--
Switch Life (No Load) (Typical)	100M	100M	100M	100M	100M	100M
Switch Life (Rated Load) (Typical) ^[5]	100K	100K	100K	100K	100K	100K
Operating Temperature	0°C - 55°C	0°C - 55°C	0°C - 55°C	0°C - 55°C	0°C - 55°C	0°C - 55°C
Storage Temperature	-20°C - 70°C	-20°C - 70°C	-20°C - 70°C	-20°C - 70°C	-20°C - 70°C	-20°C - 70°C
Humidity (non-condensing)	40°C / 80% RH	40°C/80% RH	40°C/80% RH	40°C/80% RH	40°C/80% RH	40°C/80% RH

- [1] Integration time: 0.02PLC, channel delay: 0, auto zero: off, alarm: off, scaling: off, data to internal memory (disconnect the communication of each interface), the results are measured under the DCV function.
- [2] Matching impedance is 50Ω.
- [3] The isolation between banks is greater than 40dB.
- [4] The thermocouple precision of this module depends on the LO setting rather than the temperature of the cold terminal.
- [5] Only for resistive loads.

MC3534

Digital Input/Output (DIO)						
Port 1,2,3,4	8-bit, input or output, non-isolated					
Type	Vin(L)	Vin(H)	Vout(L)	Vout(H)	Vin(H) Max	
TTL	<0.8V	>2.0V	<0.2V@I _{out} =-500mA	>4.8V@I _{out} =1mA	<42V with external open drain pull-up	
5V CMOS	<1.5V	>3.5V	<0.2V@I _{out} =-500mA	>4.8V@I _{out} =1mA		
3.3V CMOS	<1.0V	>2.3V	<0.2V@I _{out} =-500mA	>3.15V@I _{out} =1mA		
2.5V CMOS	<0.75V	>1.75V	<0.2V@I _{out} =-500mA	>2.35V@I _{out} =1mA		
User defined	Threshold-0.3V	Threshold+0.3V	<0.2V@I _{out} =-500mA	>(Level-0.2V)@I _{out} =1mA		
Alarming	Match or mismatch, maskable					

Speed	4ms (Max) alarm sampling	4ms (Max) alarm sampling
Latency	5ms	5ms
Read/Write Speed	100/s	100/s
Totalizer Input (TOT)		
	High Speed (TOT1,TOT2)	Normal Speed (TOT3,TOT4)
Maximum Count	$2^{32}-1$	$2^{32}-1$
Totalizer Input	10MHz (max), rising or falling edge, programmable	100kHz (max), rising or falling edge, programmable
Signal Level	CMOS 3.3V, 5V tolerable	1Vp-p(min), 42Vpk(max), Vcm=-12V~+12V
Threshold	Fixed at CMOS 3.3V	-12V~+12V, programmable
Gated Input	CMOS 3.3V-Hi, CMOS 3.3V-Lo or none, 5V tolerance	CMOS 3.3V-Hi, CMOS 3.3V-Lo or none, 5V tolerance
Count Reset	Manual or Read + Reset	Manual or Read + Reset
Read Speed	100/s	100/s
Analog Voltage Output (DAC)		
DAC 1,2,3,4	$\pm 12V$, non-isolated (earth referenced)	
Resolution	1mV	
Iout	10mA max	
Setting Time	1ms to 0.01 % of output	
Accuracy 1 year$\pm 5^{\circ}\text{C}$	$\pm (\% \text{ output} + \text{mV})$ 0.25%+20mV	
Temp Coefficient	$\pm(0.015\% + 1\text{mV})/\text{ }^{\circ}\text{C}$	

General Specifications

Display	4.3 inches
Power Supply	AC 100V - 120V, 45Hz - 440Hz AC 200V - 240V, 45Hz - 66Hz Detect the power frequency automatically at power-on, 400 Hz defaults to 50 Hz
Power Consumption	25 VA Max

Working Environment	Full accuracy for 0°C to 50°C Full accuracy to 80% R.H. at 40°C without condensation
Storage Temperature	-40°C to 70°C
Operation Altitude	Up to 2000m
Safety	IEC 61010-1; EN 61010-1; UL 61010-1; CAN/CSA-C22.2 No. 61010-1 Measurement CAT I 300V Pollution Degree 2
EMC	EN 61326-1
Weight	About 5.7 kg (without package)
Dimension	(height × width × length): 159.0mm × 239.0mm × 373.4mm
Remote Interface	GPIB, 10/100Mbit LAN, USB 2.0 Full Speed Device & Host (support USB storage device), RS-232
Programming Language	SCPI
LXI Compatibility	LXI Core 2011 Device, Version 1.4
Warm-up Time	90 minutes